

# Using MatrixPortal M4 for animation

## How to use MatrixPortal M4 for animation

We have another [\*\*tutorial\*\*](#) for setting up the MatrixPortal board and covering the basics. This tutorial will focus on creating an animation to display on a 64x32 matrix.

### **IMG\_5497.jpg**

#### **CircuitPython and libraries versions**

In this tutorial, we are using CircuitPython 9.0.5 (11/10/2024), all libraries and code used are compatible with this version. Please double-check the latest version of CircuitPython you have installed and use updated and compatible libraries.

## Creating the Spitesheet

A spritesheet is a single image file that contains a collection of smaller images (called sprites) arranged in a grid or some other layout. These individual sprites can represent various frames of an animation, characters, objects, or other visual elements in a video game or graphic application.

We will need to use a bitmap spitesheet. If you just want to test the code, you can download the [test.bmp](#) and skip this part for now.

### 1. Piskel

[\*\*Piskel\*\*](#) is a free online editor for animated sprites & pixel art.

#### **piskel.png**

- Go to `resize` to set the canvas size to 64 x 32 px
- Draw whatever you want
- `Add new frame` and draw
- until you finish

#### **Screenshot 2024-10-11 at 12.04.56.png**

- Go to `EXPORT`
- Select `PNG`
- Change `Columns` to 1
- `Download`
- You now have a very long PNG file

## 2. Photoshop

### bmp format.png

- Open the image with Photoshop
- Save a copy in BMP format
- Choose Windows (doesn't matter what computer you use) and 16 Bit
- You now have a ready-to-go spitesheet BMP file

## Importing the Image

1. Create a folder called `bmp` in the **CIRCUITPY** drive.
2. Copy the bitmap file you have created into the folder.

## Code

```
# SPDX-FileCopyrightText: 2020 John Park for Adafruit Industries
#
# SPDX-License-Identifier: MIT

import time
import os
import board
import displayio
from digitalio import DigitalInOut, Pull
from adafruit_matrixportal.matrix import Matrix
from adafruit_debouncer import Debouncer

SPRITESHEET_FOLDER = "/bmp"
DEFAULT_FRAME_DURATION = 0.1 # 100ms

FRAME_DURATION_OVERRIDES = {
    "KIRBY.bmp": 0.05,
}

# --- Display setup ---
matrix = Matrix(width=64, height=64, bit_depth=6)
sprite_group = displayio.Group()
matrix.display.root_group = sprite_group

file_list = sorted(
```

```
[  
    f  
    for f in os.listdir(SPRITESHEET_FOLDER)  
    if (f.endswith(".bmp") and not f.startswith("."))  
]  
)  
  
if len(file_list) == 0:  
    raise RuntimeError("No images found")  
  
current_image = None  
current_frame = 0  
current_loop = 0  
frame_count = 0  
frame_duration = DEFAULT_FRAME_DURATION  
direction = 1 #1 for forward, -1 for backward  
  
def load_image():  
    """  
    Load an image as a sprite  
    """  
    # pylint: disable=global-statement  
    global current_frame, current_loop, frame_count, frame_duration  
    while sprite_group:  
        sprite_group.pop()  
  
    filename = SPRITESHEET_FOLDER + "/" + file_list[current_image]  
  
    # # CircuitPython 7+ compatible  
    bitmap = displayio.OnDiskBitmap(filename)  
    sprite = displayio.TileGrid(  
        bitmap,  
        pixel_shader=bitmap.pixel_shader,  
        tile_width=bitmap.width,  
        tile_height=matrix.display.height,  
    )  
  
    sprite_group.append(sprite)  
  
    current_frame = 0
```

```
current_loop = 0
frame_count = int(bitmap.height / matrix.display.height)
frame_duration = DEFAULT_FRAME_DURATION
if file_list[current_image] in FRAME_DURATION_OVERRIDES:
    frame_duration = FRAME_DURATION_OVERRIDES[file_list[current_image]]
direction = 1

def advance_image():
    """
    Advance to the next image in the list and loop back at the end
    """
    # pylint: disable=global-statement
    global current_image
    if current_image is not None:
        current_image += 1
    if current_image is None or current_image >= len(file_list):
        current_image = 0
    load_image()

def advance_frame():
    """
    Advance to the next frame and loop back at the end
    """
    # pylint: disable=global-statement
    global current_frame, current_loop, direction
    current_frame += direction
    if current_frame >= frame_count:
        current_frame = frame_count - 1
        direction = -1 # Reverse direction
    elif current_frame < 0:
        current_frame = 0
        direction = 1 # Forward direction
    sprite_group[0][0] = current_frame

    advance_image()

while True:
    advance_frame()
```

```
time.sleep(frame_duration)
```

---

Revision #3

Created 11 October 2024 10:46:03 by Joanne Leung

Updated 7 July 2025 10:45:38 by Joanne Leung